








CE+T America Product Guide

		Input (DC)					
		24V	48V	110V	220V		
 STI Power up to 1 KVA Standalone High MTBF	300VA	-----	X	-----	-----	120V	Output
		X	X	-----	-----		
	600 VA	-----	X	-----	-----	120V	Output
		-----	X	-----	-----		
1,000 VA	-----	X	-----	-----	120V	Output	
	-----	X	-----	-----			230V


		Input (DC)					
		24V	48V	110V	220V		
 Arcon ST Power up to 3 KVA Standalone Built-in Static Switch High MTBF Hot Swappable	300VA	-----	X	-----	-----	120V	Output
		-----	X	-----	-----		
	600 VA	-----	X	-----	-----	120V	Output
		-----	X	-----	-----		
1,250 VA	-----	X	-----	-----	120V	Output	
	X	X	X	-----			230V
3,000 VA	X	X	-----	-----	120V	Output	
	X	X	X	X			230V


		Input (DC)					
		24V	48V	110V	220V		
 Miniflex Scalable up to 11+1 KVA Optional static switch Supports Redundancy Hot Swappable Rear Connections Connections thru subrack	1,000 VA	-----	X	-----	-----	120V	Output
		-----	X	-----	-----		


		Input (DC)					
		24V	48V	110V	220V		
 RDI Scalable up to 54 KVA Optional static switch Supports Redundancy Hot Swappable Front Connections	1,000 VA	-----	X	-----	-----	120V	Output
		-----	X	-----	-----		
	3,000 VA	X	X	-----	-----	120V	Output
		X	X	X	X		


		Input (DC)					
		24V	48V	110V	220V		
 Arcon RDI Scalable up to 72 KVA Optional static switch Supports Redundancy Hot Swappable Rear Connections Connections thru subrack	3,500 VA	-----	X	-----	-----	120V	Output
		-----	X	-----	-----		
	4,000 VA	-----	X	-----	-----	120V	Output
		-----	X	-----	-----		




			Input (DC)					
			24V	48V	110V	220V		
	TSI Veda Scalable up to 2500 VA Front AC _{out} Connection Supports redundancy Hot Swappable Rear DC Connection 1U High	500 VA per mod 1500 VA per shelf (max)					120V 230V	Output (AC)
				X				

			Input (DC)					
			24V	48V	110V	220V		
	TSI Nova Scalable up to 24 KVA Enhanced Power Conversion Feature Supports redundancy Hot Swappable Rear Connections 1U High	750 VA per mod 3000 VA per shelf (max)					120V 230V	Output (AC)
				X				

			Input (DC)					
			24V	48V	110V	220V		
	TSI Media Scalable up to 48 KVA Enhanced Power Conversion Feature Supports redundancy Hot Swappable Rear Connections 2U High	1500 VA per mod 6000 VA per shelf (max)		X			120V 230V	Output (AC)
				X				

			Input (DC)					
			24V	48V	110V	220V		
	TSI Media System Scalable up to 6 KVA Enhanced Power Conversion Feature Supports redundancy Hot Swappable Input DC Breakers Output AC Breakers Optional NEMA Outlets	1500 VA per mod 3000 VA per shelf (max)		X			120V 230V	Output (AC)
				X				

			Input (DC)					
			24V	48V	110V	220V		
	TSI Bravo Scalable up to 80 KVA Enhanced Power Conversion Feature Supports redundancy Hot Swappable Rear Connections 2U High	2500 VA per mod 10000 VA per shelf (max)		X			120V 230V	Output (AC)
				X				